


**Rackchip** Qualcomm

# ARM Architecture Industrial Computer HMI Human Machine Interface

all the BSP drivers are included



## Key Advantages

Shorten the development  
cycle for customers


Assist customers in  
shortening the procurement time





5 - 10 year-long  
product supply cycle

FAE Technical support  
Rapid Response With solution

## Installation diagram



Characteristics	Raspberry Pi	Industrial Embedded Motherboard
Stability	Average: suitable for general development and experimentation	High: can remain reliable in harsh environments
Operating Temperature Range	0°C - 70°C	0°C - 70°C (optional : -40°C - 85°C)
Anti-interference Capability	Prone to be affected by electromagnetic interference	Can work stably in a complex electromagnetic environment
Protection Level	Limited protection capabilities	High protection level against dust, water, shock, etc.
Interface Type	Limited interface type	Rich interfaces to meet diverse requirements
Reliability	Average: mainly used for non-critical applications	High: suitable for mission-critical and industrial control applications
Lifecycle	Relatively short as the product has a fast update and replacement cycle	Relatively long and usually has a multi-year supply and support cycle
Certification Standards	No strict industrial certification standards	Comply with various industrial certification standards, such as CE, ROHS
Technical Support	Forum communication , no online support provided by technical staff	1V1 FAE technical online support



# Chipset Solution



High computing power, meeting lightweight AI computing requirements


Chipset	CPU	GPU	NPU	Memory(DDR)	System
RK 3588	4*A76+4*A55 2.4GHz+1.8GHz	Mali-G610	6TOPS	4G/8G/16G/32G	Android 11 Debain11 Buildroot Ubuntu 20.04
RK 3568	4*A55 2.0GHz	Mali-G52	1TOPS	2G/4G/8G	Android 11 Debain11 Buildroot Ubuntu 18.04/20.04
RK 3566	4*A55 1.8GHz	Mali-G52	1TOPS	2G/4G/8G	Android 11 Debain 11 Buildroot Ubuntu 18.04/20.04
RK 3399	2*A72+4*A53 1.8GHz+1.4GHz	Mali-T860	/	2G/4G	Android7 ubuntu18.04
RK 3288	4*A17 1.8GHz	Mali-T764	/	2G/4G	Android 5/7
RK 3128	4*A7 1.2GHz	Mali-400	/	1G/2G	Android 5/7
RK 3576	4*A72+4*A53 2.2GHz	Mali-G52	6TOPS	2GB/4GB/8GB/16GB	Android 14 ubuntu 20.04



Native WiFi & BT & 4G & GPS/GNSS  
Advanced manufacturing process, lower energy consumption

Chipset	CPU	GPU	NPU	Memory(Ram)	System
Qualcomm 865	4*A77+4*A55 2.84GHz+1.8GHz	Adreno 650	/	8G	Android 10
Qualcomm 665	4*A73+4*A53 2.0GHz+1.8GHz	Adreno 610	/	4G	Android 10
Qualcomm 450	8*A53 1.8GHz	Adreno 506	/	2G/4G	Android 9
Qualcomm 8909	4*A7 1.1GHz	Adreno 304	/	1G	Android 7


# ARM Single Board Computer



## XB LC

Applicable to medical equipment, industrial all-in-one machines, and other fields.


Supporting 8-channel GPIO, 6-channel USB, 4G, TF card, headphone jack interfaces.



## XB NANO

Applicable to fields such as AI, edge computing, and high-algorithm processing.


Capable of connecting 8\*AHD cameras, with 4 onboard USB 3.0 interfaces.



## XB PLUS

Applicable to IoT, smart healthcare, smart cities, and other fields.

4G and 5G modules can coexist, with options of dual HDMI OUT or 1 HDMI OUT & 1 HDMI IN.



## XB PLUSX

Applicable to industrial servers, smart displays, vehicle-mounted terminals, and other fields.

With 4 onboard USB 3.0 interfaces, 3 1000M Ethernet ports, 2 HDMI OUT & 1 HDMI IN, and supports the coexistence of 4G and 5G modules.

## Specification Table

ITEMS	SOC	Storage	System	Network	CPU	Interface Signal
MST 3568XB	RK3568	2G+8G 2G+32G 4G+32G 4G+64G 8G+128G	Android11 Ubuntu 18.04	WiFi, CAN LAN,4G, GPS	Quad-core ARM-A55@2.0GHz	USB RS232 RS485 TTL UART RJ45
MST 3399XB	RK3399	2G+8G 4G+32G 4G+128G	Android 7.1 Ubuntu 18.04	WiFi, LAN 4G, GPS	Dual-core ARM-A72@1.8GHz  Quad-core ARM-A53@1.4GHz	
MST 3588XB	RK3588	4G+32G 4G+64G 8G+64G 16G+64G 16G+128G	Android12 Ubuntu20.04		Quad-core ARM-A76@2.4GHz  Quad-core ARM-A55@1.8GHz	
MST 8909XB	MSM8909	1G+8G	Android 7.1	WiFi, LAN 4G CAT4 GNSS	Quad-core ARM-A7@1.1GHz	
MST 450XB	Snapdragon 450	4GB+64GB	Android 9		Octa-core ARM-A53@1.8GHz	
MST 665XB	Snapdragon 665	4G+64G	Android 10		Quad-core ARM-A73@2.0GHz  Quad-core ARM-A53@1.8GHz	

# ARM Industrial Mini PC



## MST-RK3588XB NANO BOX

Chipset	RK3588
Model no.	MST-RK3588XB NANO BOX
Storage	4G+32G (optional: 8G+64G, 16+128G, 32GB+256GB, M.SATA)
Network	WIFI, LAN, BT
System	Android, Linux
Interface	1*RS232, 1*RS485, USB*4, HDMIOUT*1, 1000M Ethernet*1, 8-channel GPIO*1
CPU	Octa-core 64bit, Quad-core CORTEX-A76+Quad-core CORTEX-A55, Frequency up to 2.4GHz
NPU	GPU:MALI-G610 GPU, Support: OpenGL ES1.1/2.0/3.1/3.2, Vulkan 1.1/1.2/2.0, 6TOPS






## MST-RK3588XB PLUSX BOX

Chipset	RK3588
Model no.	MST-RK3588XB PLUS BOX
Storage	4G+32G (optional: 8G+64G, 16+128G, 32GB+256GB, M.SATA)
Network	WIFI, LAN, BT
System	Android, Linux
Interface	USB*4, HDMI OUT*1, HDMIIN*1(optional), 1000M Ethernet*2, UART*2
CPU	Octa-core 64bit, Quad-core COR TEX-A76+Quad-core COR TEX-A55, Frequency up to 2.4GHz
NPU	GPU:Mail-G610 GPU, Support: OpenGL ES1.1/2.0/3.1/3.2, Vulkan 1.1/1.2/2.0, 6TOPS

# ARM Industrial Display Module



**5-inch to 32-inch** high-resolution, high-brightness displays with flexible options for customization available




- Size: 5inch-32inch
- Brightness: 250nit-1500nit
- Storage: 2G+8G、4G+16G、8G+64G、16G+128G

## Specification Table

Size	System	Resolution	Internet	UART
5"	Android Linux	800X480 LVDS (option 720X1280 MIPI)	WIFI 802.11 b/g/n LAN 4G(option) GPS(option)	UART5:RS232/TTL    UART_USB:RS485 UART6:RS232/TTL
7"		1024X600 LVDS (option 800X1280 MIPI) (option 1200X1920 MIPI)		UART5:RS232/TTL    UART_USB:RS485 UART6:RS232/TTL
8"		1024X768 LVDS 800X1280 MIPI (option 1200X1920 MIPI)		UART1:RS232/TTL    UART_USB:RS485 UART3:RS232        UART4:RS232/TTL
10.1"		1024X600 LVDS (option 800X1280 MIPI) (option 1200X1920 MIPI)		UART5:RS232/TTL    UART_USB:RS485 UART6:RS232/TTL
12.1"		1280X800 LVDS		UART5:RS232        UART_USB:RS485 UART6:TTL            UART9:TTL
13.3"		1366X768 LVDS 1920X1080 eDP		UART1:RS232/TTL    UART_USB:RS485 UART3:RS232        UART4:RS232/TTL
15"		1024x768 LVDS		UART1:RS232/TTL    UART_USB:RS485 UART3:RS232        UART4:RS232
15.6"		1920X1080 eDP		UART1:RS232/TTL    UART_USB:RS485 UART3:RS232        UART4:RS232/TTL
18.5"		1366X768 LVDS (option 1920X1080 LVDS)		UART1:RS232/TTL    UART_USB:RS485 UART3:RS232        UART4:RS232/TTL
21.5"		1920X1080 LVDS		UART1:RS232/TTL    UART_USB:RS485 UART3:RS232        UART4:RS232/TTL
32"		1920X1080 LVDS		UART1:RS232/TTL    UART_USB:RS485 UART3:RS232        UART4:RS232/TTL


# ARM Industrial Panel PC



**Full-featured interface standard covering**  
Customization sizes from 5 to 43 inches

Industrial-grade touch display product for harsh environments

## Interface Description



**Can meet the requirements of a variety of interfaces**

Optional:WIFI, Bluetooth, 4G modules

72-hour production high-temperature test

8000-hour durability test

# Industrial Touch Panel Monitor



## HDMI interface, optional resolution and brightness

---

- A sturdy all-aluminum alloy body
- Wide temperature operation: -10~60°C
- Industrial-grade chip
- Industrial anti-glare and corrosion-resistant AG process
- Wide voltage power supply: DC12V - 36V
- Support multiple installation methods

# FAE Technical Support

Rapid Response With Solution



Warranty for 1 year

Repairs can be shipped back or replaced with a new one




Provide SDK Toolkit

Provide API



Product Documentation

Tutorials and Examples



# ODM Service

Applications cover a wide range of fields, including Industrial motherboard, HMI Human Machine Interface, Intelligent manufacturing and more.

## Medical Equipment



## Smart Transportation



## HMI Human Machine Interface



## Industrial All-in-one Machines



## Smart Energy




## Self-Service Vending Machine





# Customization Process



## Core Board Customization

Customized Core Board

(Compatible with existing baseboards, saving costs and development cycles, achieving perfect replacement and upgrade)

## Full Board Customization

Based on the customer's product positioning, functions, and technical requirements list, we provide comprehensive personalized customization services to meet the overall needs of the product.